

6.1 MR Image Formation

Matrix, Gradients & Signals Image formation & k-space

Carolyn Kaut Roth, RT (R)(MR)(CT)(M)(CV) FSMRT
CEO Imaging Education Associates

www.imaginged.com

candi@imaginged.com

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Outline

- Imaging Matrix
- Gradients & Signals
- Phase, Frequency and Amplitude
- Slice selection
- Phase encoding
- Frequency encoding

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 2

Objectives

Upon completion of this course, the attendee should...


1. Learn about the matrix.
2. Understand the MR signals and how they are affected by gradients
3. Learn the concept phase, frequency & amplitude.
4. Understand image formation, slice selection, phase encoding, frequency encoding
5. Understand the concept of k-space.

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.


Slide # 3

Imaging Matrix

- Digital images are created with a matrix
- Smallest unit of the digital image is a pixel



6 x 6




3 x 3

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 4

Pixel, Voxel

- In MRI slices are acquired
- The voxel is a 3d volume element
- The face of the voxel is the pixel




Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 5

What makes up a digital image?

- The size of the area imaged in MRI is the field of view (FOV)
- The number of pixels (rows x columns) is the matrix
- The depth is the slice thickness



Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 6

Calculating pixel size

- to calculate the pixel size
- to calculate the voxel size

Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved.

Slide # 7

Imaging

Calculating pixel & voxel size

- Isotropic voxel

$$\frac{\text{FOV}}{\text{Matrix}} = \frac{\text{FOV}}{\text{Matrix}} = \text{Thickness}$$
- Pixel size

$$\frac{\text{FOV}}{\text{Matrix}} \times \frac{\text{FOV}}{\text{Matrix}}$$
- Area of the Pixel (mm^2)

$$\frac{\text{FOV}}{\text{Matrix}} \times \frac{\text{FOV}}{\text{Matrix}}$$
- Voxel Volume (mm^3)

$$\frac{\text{FOV}}{\text{Matrix}} \times \frac{\text{FOV}}{\text{Matrix}} \times \text{Thickness}$$

Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved.

Slide # 8

Imaging

Pixel Size and Matrix

- higher matrix
- smaller pixel
- less tissue in the pixel
- higher resolution

Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved.

Slide # 9

Imaging

Pixel Size and FOV

- smaller FOV
- smaller pixel
- less tissue in the pixel
- higher resolution

Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved.

Slide # 10

Imaging

Pixel Size and Slice thickness

- smaller thickness
- smaller pixel
- less tissue in the pixel
- higher resolution

Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved.

Slide # 11

Imaging

Imaging Planes

- What Views (Planes)
 - Sagittal
 - Axial
 - Coronal
 - Oblique
- What Contrast
 - TR
 - TE


Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved.

Slide # 12

Imaging

To Create MR Images

- The patient is placed in the magnetic field
 - to align the spins
- The RF pulse is applied
 - to excite the spins
 - at the Larmor Frequency



Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 13


Timing Diagrams – RF & Gradient Pulses

TR, is the time between 90° RF pulses

These lines represent gradient pulses

MR signal induced in the receiver coil

TE (Echo Time)




Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 14

Short & Long TR Imaging

Short TR

Long TR



Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 15

MR Excitation Relaxation


Alignment

Excitation

Relaxation

MR Signal FID

RF Receiver coil



Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 16


Timing Diagram

TR (Repetition Time)

TE (Echo Time)

Image with artifact

Cleaned up the "SIC"



Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 17

Timing Diagram -TE

Proton density-TE1

T2WI-TE2


T2 decay

FID

echo

TE 1


TE 2



Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 18


Imaging Planes

- What Views (Planes)
 - Sagittal
 - Axial
 - Coronal
 - Oblique
- What Contrast
 - TR
 - TE




Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 19

Imaging Planes



Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 20


Timing Diagram – Gradients- logical coordinate system



Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 21

Slice Selection


- If the magnetic field is homogeneous, the frequency is the same ... head to feet
- If the RF is applied... in this case the entire body would be excited



Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 22


Selective Excitation

- To excite a location within the imager, within the body..
- A magnetic field gradient is applied
- The RF pulse is applied that matches a location



Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 23

Selecting an Axial Slice – Physical Coordinate System



Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 24

Selecting a Coronal Slice - Physical Coordinate System

Y gradient
Anterior to Posterior

Coronal slice

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 25

Imaging

Selecting a Sagittal Slice - Physical Coordinate System

X gradient
Right to Left

Sagittal slice

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 26

Imaging

Phase & Frequency Encoding

- Once the slice is selected...
- Encoding along the other axes,
 - With gradients
 - R to L
 - A to P
 - For encoding
 - Phase encoding
 - Frequency encoding

Gradient S to I

Gradient R to L

Gradient A to P

Axial slice selection

Axial slice

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 27

Imaging

Outline

- Imaging Matrix
- Gradients & Signals
- Phase, Frequency and Amplitude
- Slice selection
- Phase encoding
- Frequency encoding

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 28

Imaging

Periodic signals

Phase
Frequency
Amplitude
Wavelength

wavelength

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 29

Imaging

Amplitude

Low Amplitude Signal

Medium Amplitude Signal

High Amplitude Signal

Enhanced Brain Image

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 30

Imaging

Frequency

Periodic signal
Sine wave
Frequency = # times it repeats in a period of time
cycles per second or Hertz (Hz)
or million cycles per second, or megahertz (MHz)

Revolutions along the precessional path

1 second

1 cycles per second

2 cycles per second

4 cycles per second

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 31

Imaging

Phase

What phase of the precession
where along the precessional path
In phase
Out of phase

In Phase

Out of phase

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 32

Imaging

Phase & Frequency

90 degrees

0 degrees

180 degrees

360 degrees

270 degrees

Frequency is the *rate of precession*
Phase is a *position* along a precessional path

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 33

Imaging

Phases of Periodic Signals

0 degrees

90 degrees

180 degrees

270 degrees

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 34

Imaging

Changing the Frequency and Phase

Steep Gradient
High Amplitude Gradient

Low Gradient
Low Amplitude Gradient

High changes in frequencies
Big changes in phase

Small changes in frequencies
Small changes in phase

De phased
Low signal
Low amplitude signal

In phase
High signal
High amplitude signal

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 35

Imaging

Signal Amplitude

Phase & Frequency = Where

Amplitude = What color

Black – Low Amplitude
Gray – Medium Amplitude
White – High amplitude

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 36

Imaging

Phase & Frequency

Phase & Frequency = Where
Same frequency – different phase

Same phase different frequency

Same phase and frequency,
different amplitude

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 37

Imaging

K-Space & MR Imaging

Amplitude = What color
Black, low
Gray, med
White, high amplitude signal

Phase & Frequency = Where
Phase lines in k-space
Frequency – points along each line

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 38

Imaging

CT Image Acquisition

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 39

Imaging

Back Projection

In CT, the x-ray tube rotates around the "phantom"
In this case the x-ray beam is attenuated by the water in the phantom,
and therefore "projects" a "shadow" within the detectors...

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 40

Imaging

Back Projection - Reconstruction

Where the lines intersect,
there could be water in the phantom
Two projections are not enough!

The third projection allowed for the image!

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 41

Imaging

MR Image Formation

- In order to define a point in space, we need three coordinates X, Y & Z
- To define these three coordinates, we do 3 jobs
 - slice selection
 - phase encoding
 - frequency encoding

3 x 3 Matrix


Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 42

Imaging

Outline

- Imaging Matrix
- Gradients & Signals
- Phase, Frequency and Amplitude
- Slice selection
- Phase encoding
- Frequency encoding




Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved.

Slide # 43

Imaging

Timing Diagram - Logical Coordinate System



Gradients

- SS (Z)
 - Slice selection gradient
- PE (Y)
 - Phase encoding gradient
- FE (X)
 - Frequency encoding gradient

MR signal


Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved.

Slide # 44

Imaging

Slice Selection

- If the magnetic field is homogeneous, the frequency is the same ... head to feet
- If the RF is applied... in this case the entire body would be excited



Homogeneous magnetic field
The frequency is the same from the head to the feet


Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved.

Slide # 45

Imaging

Selective Excitation

- To excite a location within the imager, within the body..
- A magnetic field gradient is applied
- The RF pulse is applied that matches a location



Homogeneous magnetic field
With a linear gradient field applied


Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved.

Slide # 46

Imaging

Slice Thickness & Transmitter Bandwidth

- If only one frequency is "sent in" or transmitted for excitation, we get a slice as thin as tissue paper.
- For a thicker slice a range of frequencies is "transmitted" known as the Transmit Bandwidth



This radiofrequency matches the location in the mid section of this patient, hence a thin axial slice in the belly

FYI... This is not the bandwidth that we typically "set" during image acquisition. That is the receiver bandwidth. Receive bandwidth will be discussed later in this section

This range of radiofrequencies (or Bandwidth) matches the location in the mid section of this patient, hence a thin axial slice in the belly


Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved.

Slide # 47


Imaging

Slice Thickness & Gradient Amplitude

- Steep Gradients (high amplitude) slice selection gradient, produce thin slices.
- Flatter Gradients (low amplitude) slice selection gradient, produce thicker slices.
- "Steep things make skinny things!"



With a given BW, a steep gradient produces a thinner slice



With a given BW, a flatter gradient produces a thicker slice

Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved.

Slide # 48

Imaging

Imaging Planes & Slice Selection Gradients

RF pulses for spin echo
Z gradient

Axial slice
Z gradient
Superior to Inferior

Coronal slice
Y gradient
Anterior to Posterior

Sagittal slice
X gradient
Right to Left

The gradient used for oblique depend upon the oblique desired
Z & Y gradient
Anterior to Posterior

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 49

Physical vs Logical Gradients

Logical Gradients

Z
Slice Selection

Y
Phase Encoding

X
Frequency Encoding

Physical Gradients

- Slice Selection
Z (runs superior to inferior) (axial)
Y (A-P) (coronal)
X (R-L) (sagittal)
- Phase Encoding
- Depends upon the plane
smaller word
smaller anatomy (motion)
smaller matrix (time)
- Frequency Encoding
- Depends upon the plane

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 50

Spatial Encoding within the Slice

- Once the slice is selected
- Encoding along the other axes,
 - With gradients
 - R to L
 - A to P
 - For encoding
 - Phase encoding
 - Frequency encoding

Gradient S to I
Axial slice selection

Gradient A to P

Gradient R to L

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 51

Spatial Encoding within the Slice

Fourier states that any "shape" can be reconstructed by periodic signals

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 52

Fourier Transformation – Step #1

Sine wave

Ramp

Step #1

- Let's take one sine wave and
- Try to produce a "ramp"

• Not Even close...

Storage space

K-space

? Image

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 53

Fourier Transformation – Step #2

Sine wave

Ramp

Step #2

- Let's take another sine wave with lower amplitude and higher frequency
- And try again

• Better...

Storage space



K-space

? Image

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 54





Fourier Transformation – Step #3

Step #3



- Let's take another sine wave with lower amplitude and higher frequency
- And try again

•Better but no cigar!

Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 55





Fourier Transformation – step #4

Step #4



- Let's take another sine wave with lower amplitude and higher frequency
- And try again

•Not Bad!

Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 56

Truncation Artifact – 2D Fourier Transform (2DFT)

Truncation Artifact



Less Samples

More Samples

Virtually no visible truncation Artifact




Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 57

K-space - Sampling

Center of K-space for Contrast
Signal to Noise

Edges of K-space
Detail
Resolution



Storage space

K-space

Image

Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 58



Image Formation & K-space filling

K-space for Mona Lisa
All lines filled

Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 59

Image Formation & K-space filling





K-space for Mona Lisa
Edges Filled

Resolution
But no contrast...

Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 60

Image Formation & K-space filling



K-space for Mona Lisa
Center lines filled




Contrast but
No resolution...

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.


Slide # 61



Fourier Transformation



K-space for Mona Lisa
All lines filled



Fourier transformer will do FT, one at a time
Array processor will do an "array" of FT's


Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 62




Let's Make an MR Image...

- Select a slice
- Encode along the other axes,
 - With gradients
 - R to L
 - A to P
 - Encoding Steps
 - Phase encoding
 - Frequency encoding



Axial slice selection



Gradient
A to P
Gradient
R to L

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 63



Outline


- Imaging Matrix
- Gradients & Signals
- Phase, Frequency and Amplitude
- Slice selection
- Phase encoding
- Frequency encoding

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 64



Image Acquisition & Image Formation



Timing Diagram

K-space
Not the image (raw data)

Image
matrix (# phase & # frequency steps)


Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 65




Sampling MR Signal

- Signals are created by a 90° and a 180° pulse
- Signals are sampled during "readout" at TE
- Points are "stored" in k-space for until enough points are sampled to create an MR Image



K-space sampling points




TE

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 66



Nyquist Theorem




- Signals must be sampled at least twice per cycle
- This means that they must be sampled at the highest frequency
- Sampling is performed at a given time interval (t) based on the frequency

Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 67



Aliasing



- If signals are not sampled at the appropriate time interval
- Signals are not sampled properly
- This results in aliasing


Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 68



K-Space

- K-space has lines, # Phase encoding steps
- And points along each line, # Frequency steps




Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 69



K-Space

- Steep (-) phase encoding gradient
- Sample the echo
- "Store" in k-space




Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 70



Image Formation

- Less Steep (-) phase encoding gradient
- Sample the echo
- "Store" in k-space




Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 71









K-Space



Copyright 2006 Imaging Education Associates, LLC.
All Rights Reserved.

Slide # 72





Motion Artifact



Outline

- Imaging Matrix
- Gradients & Signals
- Phase, Frequency and Amplitude
- Slice selection
- Phase encoding
- Frequency encoding
- k-space manipulation




Filling k-space

*Assume 256 phase matrix for this entire module

Remember:

The amplitude of the phase encoding gradient applied during the FID "encodes" the sampled echo for a particular phase "line" or "profile" in k-space




Linear Filling

Fills from "bottom" up

Remember:


X = Frequency
Y = Phase
Z = Slice



Centric Filling

Fills from "Middle" out

This technique acquires high signal data "lines" first
Often used in Contrast Enhanced MRA studies




Elliptic Filling

Fills from "Center" out

This technique acquires the most "central" data points first

3D acquisition used for Contrast Enhanced MRA to minimize venous filling



Number of Signals Averaged (NSA)

Scan Time = $TR \times N_y \times \underline{NSA}$

Think of the NSA as "coats of paint"
It's the number of times each "line" or "phase view" of k-space is sampled

Image courtesy Dr. Val Runge

Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 85

Reducing NSA

Scan Time = $TR \times N_y \times \underline{NSA}$

Reducing NSA

- Reduces scan time
- DOES NOT reduce spatial resolution
- Increases noise (reduces SNR)
- Increased flow/motion artifacts

Image courtesy Dr. Val Runge

Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 86

Partial Fourier

Scan Time = $TR \times N_y \times \underline{NSA}$

Partial Fourier reduces scan time at the cost of increased noise (reduced SNR)
Spatial Resolution is Unaffected

Image courtesy Dr. Val Runge

Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 87

Reducing Phase Matrix

Scan Time = $TR \times N_y \times \underline{NSA}$

GP

Image courtesy Dr. Val Runge

Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 88

Zero Fill

Scan Time = $TR \times N_y \times \underline{NSA}$

Image courtesy Dr. Val Runge

Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 89

Zero Fill

Scan Time = $TR \times N_y \times \underline{NSA}$







Reducing N_y

- Reduces Scan Time
- Reduces Spatial Resolution
- Increased SNR
- Increases Truncation Artifact

* Note: the number of phase encodings may be selected by scan percentage

Image courtesy Dr. Val Runge

Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 90



Benefits of Fast Spin Echo

Sample Scan Time

TR x Ny x NSA

3000 TR x 256 phase x 2 NSA = 25.6 minutes !


Same scan with FSE and ETL of 16 = 1.6 minutes !!

500 TR
1500 TR
3000 TR
5000 TR

Images with bright fluid often show pathology best due to presence of water

The long T1-relaxation time of water requires longer TR times to obtain images with bright fluid


Scan time increases with increasing TR



Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 97

Echo Planar Imaging (EPI)

Spin Echo EPI



Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 98

EPI Speed Compared to FSE

FSE


90 180 echo 180 echo 180 echo 180 echo

EPI

90 180 echo echo echo echo echo echo echo

SS-EPI 4 sec whole brain (1.5T)

FSE 25 sec whole brain (3T)



Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 99

Summary


Scan Time = TR x Ny x NSA

How many lines of acquisition?

- Zero-fill
- Reduced NSA
- Partial Fourier
- Rectangular FOV (Parallel Imaging)

Reducing scan time by altering the way k-space is filled typically reduces either spatial resolution or SNR


Since reduced spatial resolution is almost always undesirable, therefore, most advanced imaging techniques are SNR starved



Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 100

Outline

- Imaging Matrix
- Gradients & Signals
- Phase, Frequency and Amplitude
- Slice selection
- Phase encoding
- Frequency encoding



Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved. Slide # 101

6.1 MR Image Formation


Matrix, Gradients & Signals

Image formation & k-space

Thank you for your attention!

Click to take your post test and get your credits

Carolyn Kaut Roth, RT (R)(MR)(CT)(M)(CV) FSMRT
CEO Imaging Education Associates
www.imaginged.com candi@imaginged.com



Copyright 2006 Imaging Education Associates, LLC. All Rights Reserved.